



# Blackout™ Dock Shelter



The best way to reduce cooling loss for your large fleets  
**The ultimate climate control shelter**

Maintaining constant temperature control, avoiding energy loss, effectively sealing varying trailer configurations, and meeting regulatory requirements are real issues. Additionally, air ride suspension and intermodal trailers create more abrasive movement on dock shelters.

The Serco Blackout™ model BDS-S Dock Shelter is specifically designed for the most demanding applications.

## Features:

1. Exclusive S-900DD DryDock® Integral system effectively blocks moisture infiltration from the top of the trailer.
2. Exclusive Hinge Guard™ seals off hinge gap around swing outdoors, blocking air and light from entering the facility.
3. Exclusive UHWR (Ultra High Wear Resistant) fabric on top and bottom wear panels where heaviest trailer abrasion occurs. Tested and certified to 40,000+ abrasion cycles which is up to ten times the abrasion resistance of the competitive fabrics tested.
4. Exclusive LightBlockr™ connector curtain blocks air and light infiltration at overlap of side and head curtains.
5. Structural, rigid head frame acts as a canopy while translucent top cover allows increased visibility and operating light.
6. Exclusive roll-formed, galvanized steel framing extends product life and is superior to wood construction.
7. Foam-filled side members provide protection from impact by off-center trailers.



### DRYDOCK® MOISTURE SEALING SYSTEM

- Integral to the Blackout Dock Shelter to automatically position and seal the top of the trailer.
- High-resilient foam core protected by three layers of durable coated fabric.
- Canopy style rigid head frame increases structural integrity while translucent head member allows operating light.
- Weighted side covers provide extra protection for the dock area.



### HINGE GUARD™ GAP SEALING SYSTEM

- Integral to the Blackout Dock Shelter to automatically position and seal the trailer door hinge gaps.
- High Molecular Weight Polyethylene (HMWPE) material capable of withstanding harsh weather conditions and high cycle traffic.
- Hinge Guard specifically shaped and sized to interface with swing out door trailers of varying configurations.
- Attached securely with industrial hook and loop for easy replacement.



39-45 Della Torre Road, Moe Victoria 3825

t: 1800 674 566

e: sales@safetech.com.au

**safetech.com.au**

